


Thank you for your purchase of Orbital Expo Truss Extreme. These instructions show how erect the kit you purchased.


The color coded section will help identify the location of each part.



Each Orbital Truss Extreme kit has been carefully designed and developed to be stable and safe. Consult with your dealer for load bearing specifications. The manufacturers of Orbital Expo Truss Extreme will not be held responsible or accountable for damage or injury caused by exceeding guidelines or though wrongful/incorrect use of the system. NOTE: S = Brushed Silver Finish, WD = American Natural Wood Finish. Kits will come with choice of lights except for Lumina 2.

Graphic Specs & Art Guidelines: Arcturus, 10' x 20' Kit







	96.25"	+	• 96.25"	- 39,5"-+
BS OR-G-AR-1	BS OR-G-AR-2	BS OR-G-AR-3	BS OR-G-AR-2	BS OR-G-AR-1
Notched @ top and bottom right side. Inward hinged right side.	Notched @ all 4 corners. Inward hinged right and left sides.	Notched @ all 4 corners. Inward hinged right and left sides.	Notched @ all 4 corners. Inward hinged right and left sides.	Notched @ top and bottom left side. Inward hinged left side.

<u>Available Graphics:</u> Dye-Sublimation Graphics Only	Acceptable File Formats: Illustrator CS3 or below Photoshop CS3 or below	Bleeds: All orbital truss graphics require specific bleeds. The sizes listed above represent the finished graphic size. Please keep all logos, type, and critical information at least 1" in from each edge of the finished graphic. Dye Sublimation: 2" bleed around the perimeter. Inkjet & UV: 1/2" bleed around the perimeter.	Color: All files are printed as CMYK format. All critical Pantone colors need to be called out in the file or specified on the order as Coated or Uncoated swatches. Resolution: All raster files (either print files or linked files) must be at 100-120 pixels per inch at 100%.	 Finishing Details: When graphics are notched, a 7/8 square is cut in the appropriate location FS: Graphics mounted to front of the truss system BS: Graphics mounted to back of the truss system Dye Sublimation graphics are attached to truss with velcro. Inkjet & UV panels are attached to truss with magnet.
--	--	--	---	---

IMPORTANT INFORMATION REGARDING GRAPHIC FILES: Each graphic has a specific code or number located on the graphic. The electronic print ready files provided must be named accordingly. Using this coding system will allow us to preflight and prepare your files for print more efficiently. If you fail to provide your graphic files in this format, additional charges may be necessary to complete your printed materials.


3D Rendering: Arcturus, 10' x 20' Kit
















Color Coded Components: Arcturus, 10' x 20' Kit

-21



